



markilux awning covers

Fabric pattern series | Their limitations and manufacture

Vertical blinds, glass roof awnings and the markilux pergola compact

Designer blinds and awnings for windows	Vertical cassette blinds	markilux 776 / 776 tracfix	.01
		markilux 876 / 876 tracfix	.02
		markilux 625 tracfix	.03
		markilux 620 tracfix	.04
		markilux 710	.05
Glass roof awnings	Drop-arm cassette awning	markilux 730	.06
	Marquisolette	markilux 740	.07
	Above-glass awnings	markilux 770 tracfix	.08
Awning System	Underglass awnings	markilux 870 tracfix	.09
		markilux 779 / 779 tracfix	.10
		markilux 879 / 879 tracfix	.11
	Pergola awnings	markilux pergola compact	.12

markilux GmbH + Co. KG

Hansestrasse 53, 48282 Emsdetten

Telephone +49 (0) 25 72/15 31-0

Fax +49 (0) 25 72/15 31-6 82

info@markilux.com

WEEE registration no. DE 11340537

We reserve the right to make technical alterations without giving prior notice.

Up-to-date technical information can be found in the password-protected dealer access area at **pro.markilux.com**. All the dimensions quoted are close approximations.

sunvas
transolair
perla FR

Fabric pattern 300.. – 315..
339..
371..³⁾ / 372..³⁾

smart art
sunsilk

340..
324.. / 328.. / 369..

Fabric width 120 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

sunvas

Fabric pattern 31008²⁾, -09²⁾, -13, -16, -18, -25, -27, -28, -31, -36, -37, -57, -58, 31109, -14, -17

Fabric width 250 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		243									
		300			2)	2)	2)				
		313			2)	2)	2)				
		400			2)	2)					
		450			2)	2)					
		500			2)	2)					
		550			2)	2)					
		600			2)	2)					

2) also available in fabric width 320 cm – then seamless

sunbow

Fabric pattern 411.. - 427..

Fabric width 120 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350	3)	3)	3)	3)	3)	3)	3)	3)	3)
		400	3)	3)	3)	3)	3)	3)	3)	3)	
		450									
		500									
		550									
	600										

3) Only in tracfix units

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

 = vertical panel joints

(panel width approx. 120 cm)

 = seamless

 = horizontal panel joint(s)

 = not available

AH = unit height

1) = optional

dimensions in cm

transolair Fabric pattern 338..
Fabric width 250 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		243									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

perfortex Fabric pattern 331.. / 332..
Fabric width 120 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

vuscreen Alu Fabric pattern 317..
Fabric width 252 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		243									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

glass fibre screen Serge 600 (only available with tracfix) Fabric pattern 272..

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

 = vertical panel joints

(panel width approx. 120 cm)

 = seamless

 = horizontal panel joint(s)

 = not available

AH = unit height

1) = optional

dimensions in cm

Soltis Veozip(only available with tracfix) Fabric pattern 511..

Fabric width 290 cm

		Awning fixture width									
		150	180	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

Soltis Perform 92 Fabric pattern. 92-..

Fabric width 177 cm

		Awning fixture width									
		150	180	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm
 = vertical panel joints

(panel width approx. 120 cm)

 = seamless

 = horizontal panel joint(s)

 = not available
AH = unit height**1)** = optional

dimensions in cm

sunvas
transolair
perla FR

Fabric pattern

300.. – 315..
339..
371..³⁾ / 372..³⁾
smart art
sunsilk
340..
324.. / 328.. / 369..

Fabric width 120 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

sunvasFabric pattern 31008²⁾, -09²⁾, -13, -16, -18, -25, -27, -28, -31, -36, -37, -57, -58, 31109, -14, -17

Fabric width 250 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		243									
		300			2)	2)	2)				
		313			2)	2)	2)				
		400									
		450									
		500									
		550									
		600									

2) also available in fabric width 320 cm – then seamless

sunbow

Fabric pattern 411.. - 427..

Fabric width 120 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350	3)	3)	3)	3)	3)	3)	3)	3)	3)
		400	3)	3)	3)	3)	3)	3)	3)	3)	
		450									
		500									
		550									
		600									

3) Only in tracfix units

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm
 = vertical panel joints

(panel width approx. 120 cm)

 = seamless

 = horizontal panel joint(s)

 = not available

AH = unit height

1) = optional

dimensions in cm

transolair Fabric pattern 338..
Fabric width 250 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		243									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

perfortex Fabric pattern 331.. / 332..
Fabric width 120 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

vuscreen Alu Fabric pattern 317..
Fabric width 252 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		243									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

glass fibre screen Serge 600 (only available with tracfix) Fabric pattern 272..

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

 = vertical panel joints

(panel width approx. 120 cm)

 = seamless

 = horizontal panel joint(s)

 = not available

AH = unit height

1) = optional

dimensions in cm

Soltis Veozip(only available with tracfix)Fabric pattern 511..
Fabric width 290 cm

		Awning fixture width									
		150	180	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

Soltis Perform 92 Fabric pattern. 92-..
Fabric width 177 cm

		Awning fixture width									
		150	180	250	300	350	400	450	500	550	600
AH	tracfix 1)										
	150										
	180										
	250										
	300										
	350										
	400										
	450										
	500										
	550										
600											

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
(panel width approx. 120 cm)

= seamless
 = horizontal panel joint(s)

= not available

1) = optional

AH = unit height

dimensions in cm

sunvas
transolair
perla FR

 Fabric pattern 300.. – 315..
 339..
 371.. / 372..

smart art
sunsilk

 340..
 324.. / 328.. / 369..

Fabric width 120 cm

		Awning width									
		150	200	250	300	350	400	450	500	550	600
AH	150										
	200										
	250										
	300										
	350										
	400										

sunvasFabric pattern 31008..¹⁾, -09¹⁾, -13, -16, -18, -25, -27, -28, -31, -36, -37, -57, -58, 31109, -14, -17

Fabric width 250 cm

		Awning width									
		150	200	250	300	350	400	450	500	550	600
AH	150										
	200										
	246										
	300				1)	1)	1)				
	350				1)	1)					
	400				1)	1)					

1) also available in fabric width 320 cm – then seamless

sunbow

Fabric pattern 411.. – 427..

Fabric width 120 cm

		Awning width									
		150	200	250	300	350	400	450	500	550	600
AH	150										
	200										
	250										
	300										
	350										
	400										

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm
 = vertical panel joints

(panel width approx. 120 cm)

 = seamless

 = horizontal panel joint(s)

 = not available

AH = unit height

dimensions in cm

transolair Fabric pattern 338..
Fabric width 250 cm

		Awning width									
		150	200	250	300	350	400	450	500	550	600
AH	150										
	200										
	246										
	300										
	350										
	400										

perfortex Fabric pattern 331.. / 332..
Fabric width 120 cm

		Awning width									
		150	200	250	300	350	400	450	500	550	600
AH	150										
	200										
	250										
	300										
	350										
	400										

vuscreen Alu Fabric pattern 317..
Fabric width 252 cm

		Awning width									
		150	200	250	300	350	400	450	500	550	600
AH	150										
	200										
	248										
	300										
	350										
	400										

glass fibre screen Serge 600 Fabric pattern 272..
Fabric width 250 cm

		Awning width									
		150	200	250	300	350	400	450	500	550	600
AH	150										
	200										
	266										
	300										
	350										
	400										

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
 (panel width approx. 120 cm)
 = seamless
 = not available
 AH = unit height

dimensions in cm

Soltis Veozip Fabric pattern 511..

Fabric width 290 cm

		Awning width									
		150	200	250	300	350	400	450	500	550	600
AH	150										
	200										
	250										
	300										
	350										
	400										

Soltis Perform 92 Fabric pattern . 92-..

Fabric width 177 cm

		Awning width									
		150	177	250	300	350	400	450	500	550	600
AH	150							2)	2)		
	173							2)	2)		
	250							2)	2)		
	300							2)	2)		
	350										
	400										

2) Panel width approx. 88,5 cm

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
 (panel width approx. 120 cm)
 = seamless
 = not available
 AH = unit height

dimensions in cm

sunvas
transolair
perla FR

 Fabric pattern 300.. – 315..
 339..
 371.. / 372..

smart art
sunsilk

 340..
 324.. / 328.. / 369..

Fabric width 120 cm

		Awning width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

sunvasFabric pattern 31008..¹⁾, -09¹⁾, -13, -16, -18, -25, -27, -28, -31, -36, -37, -57, -58, 31109, -14, -17

Fabric width 250 cm

		Awning width						
		150	200	250	300	350	400	450
AH	150							
	200							
	246							
	300				1)			
	350				1)			
	400				1)			

1) also available in fabric width 320 cm – then seamless

sunbow

Fabric pattern 411.. - 427..

Fabric width 120 cm

		Awning width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm
 = vertical panel joints

(panel width approx. 120 cm)

 = seamless

 = horizontal panel joint(s)

 = not available

AH = unit height

dimensions in cm

transolair Fabric pattern 338..
Fabric width 250 cm

		Awning width						
		150	200	250	300	350	400	450
AH	150							
	200							
	246							
	300							
	350							
	400							

perfortex Fabric pattern 331.. / 332..
Fabric width 120 cm

		Awning width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

vuscreen Alu Fabric pattern 317..
Fabric width 252 cm

		Awning width						
		150	200	250	300	350	400	450
AH	150							
	200							
	248							
	300							
	350							
	400							

glass fibre screen Serge 600 Fabric pattern 272..
Fabric width 250 cm

		Awning width						
		150	200	250	300	350	400	450
AH	150							
	200							
	266							
	300							
	350							
	400							

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
 (panel width approx. 120 cm)
 = seamless
 = not available
 AH = unit height

= horizontal panel joint(s)

dimensions in cm

Soltis Veozip Fabric pattern 511..
Fabric width 290 cm

		Awning width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

Soltis Perform 92 Fabric pattern . 92-..
Fabric width 177 cm

		Awning width						
		177	200	250	300	350	400	450
AH	150					2)	2)	2)
	173					2)	2)	2)
	250					2)	2)	2)
	300					2)	2)	2)
	350							
	400							

2) Panel width approx. 88,5 cm

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
(panel width approx. 120 cm)

= seamless

= horizontal panel joint(s)

= not available

AH = unit height

dimensions in cm

sunvas
transolair
perla FR

 Fabric pattern 300.. – 315..
 339..
 371.. / 372..

smart art
sunsilk

 340..
 324.. / 328.. / 369..

Fabric width 120 cm

		Awning width								
		100	150	200	250	300	350	400	450	500
AH	150									
	200									
	250									
	300									
	350									

sunvasFabric pattern 31008..¹⁾, -09¹⁾, -13, -16, -18, -25, -27, -28, -31, -36, -37, -57, -58, 31109, -14, -17

Fabric width 250 cm

		Awning width								
		100	150	200	250	300	350	400	450	500
AH	150									
	200									
	240									
	300					1)	1)			
	350					1)	1)			

1) also available in fabric width 320 cm – then seamless

sunbow

Fabric pattern 411.. - 427..

Fabric width 120 cm

		Awning width								
		100	150	200	250	300	350	400	450	500
AH	150									
	200									
	250									
	300									
	350									

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm
 = vertical panel joints
 (panel width approx. 120 cm)

 = seamless
 = horizontal panel joint(s)

 = not available
AH = unit height

dimensions in cm

transolair Fabric pattern 338..
Fabric width 250 cm

		Awning width								
		100	150	200	250	300	350	400	450	500
AH	150									
	200									
	240									
	300									
	350									

perfortex Fabric pattern 331.. / 332..
Fabric width 120 cm

		Awning width								
		100	150	200	250	300	350	400	450	500
AH	150									
	200									
	250									
	300									
	350									

vuscreen Alu Fabric pattern 317..
Fabric width 252 cm

		Awning width								
		100	150	200	250	300	350	400	450	500
AH	150									
	200									
	250									
	300									
	350									

glass fibre screen Serge 600 Fabric pattern 272..
Fabric width 250 cm

		Awning width								
		100	150	200	250	300	350	400	450	500
AH	150									
	200									
	250									
	300									
	350									

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
 (panel width approx. 120 cm)
 = seamless
 = horizontal panel joint(s)
 = not available
 AH = unit height

dimensions in cm

Soltis Veozip (not available) Fabric pattern 511..
Fabric width 290 cm

		Awning width								
		100	150	185	250	300	350	400	450	500
AH	150									
	200									
	250									
	300									
	350									

Soltis Perform 92 Fabric pattern. 92-..
Fabric width 177 cm

		Awning width								
		100	150	185	250	300	350	400	450	500
AH	150									
	172									
	250									
	300									
	350									

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
(panel width approx. 120 cm)

= seamless
 = horizontal panel joint(s)

= not available
AH = unit height

dimensions in cm

sunvas
transolair
perla FR

 Fabric pattern 300.. – 315..
 339..
 371.. / 372..

smart art
sunsilk

 340..
 324.. / 328.. / 369..

Fabric width 120 cm

		Awning width												
		100	150	200	250	300	350	400	450	500	550	600	650	700
AL	80													
	100													
	120													
	150													

sunvasFabric pattern 31008..¹⁾, -09¹⁾, -13, -16, -18, -25, -27, -28, -31, -36, -37, -57, -58, 31109, -14, -17

Fabric width 250 cm

		Awning width												
		100	150	200	250	300	350	400	450	500	550	600	650	700
AL	80													
	100													
	120													
	150													

1) also available in fabric width 320 cm – then seamless

sunbow

Fabric pattern 411.. – 427..

Fabric width 120 cm

		Awning width												
		100	150	200	250	300	350	400	450	500	550	600	650	700
AH	80													
	100													
	120													
	150													

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm
 = vertical panel joints

(panel width approx. 120 cm)

 = seamless

 = horizontal panel joint(s)

 = not available
A = arm length

Dimensions in cm

transolair Fabric pattern 338..
Fabric width 250 cm

		Awning width												
		100	150	200	250	300	350	400	450	500	550	600	650	700
AL	80													
	100													
	120													
	150													

perfortex Fabric pattern 331.. / 332..
Fabric width 120 cm

		Awning width												
		100	150	200	250	300	350	400	450	500	550	600	650	700
AL	80													
	100													
	120													
	150													

vuscreen Alu Fabric pattern 317..
Fabric width 252 cm

		Awning width												
		100	150	200	250	300	350	400	450	500	550	600	650	700
AL	80													
	100													
	120													
	150													

glass fibre screen Serge 600 Fabric pattern 272..
Fabric width 250 cm

		Awning width												
		100	150	200	250	300	350	400	450	500	550	600	650	700
AL	80													
	100													
	120													
	150													

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
 (panel width approx. 120 cm)
 = seamless
 = not available
 A = arm length

Dimensions in cm

Soltis Veozip (not available) Fabric pattern 511..
Fabric width 290 cm

		Awning width												
		100	150	185	250	300	350	400	450	500	550	600	650	700
AL	80													
	100													
	120													
	150													

Soltis Perform 92 Fabric pattern. 92-..
Fabric width 177 cm

		Awning width												
		100	150	185	250	300	350	400	450	500	550	600	650	700
AL	80													
	100				2)	2)	2)	2)	2)	2)	2)	2)	2)	2)
	120													
	150													

2) horizontal seam from cover length 173 cm

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
(panel width approx. 120 cm)

= seamless

= horizontal panel joint(s)

= not available

AH

= unit height

1) = optional

dimensions in cm

sunvas
transolair
perla FR

 Fabric pattern 300.. – 315..
 339..
 371.. / 372..

smart art
sunsilk

 340..
 324.. / 328.. / 369..

Fabric width 120 cm

		Awning width				
		100	150	200	250	300
AH	120					
	160					
	200					
	250					
	300					

sunvasFabric pattern 31008..¹⁾, -09¹⁾, -13, -16, -18, -25, -27, -28, -31, -36, -37, -57, -58, 31109, -14, -17

Fabric width 250 cm

		Awning width				
		100	150	200	250	300
AH	120					
	160					
	200					
	250					
	300					1)

1) also available in fabric width 320 cm – then seamless

sunbow

Fabric pattern 411.. - 427..

Fabric width 120 cm

		Awning width				
		100	150	200	250	300
AH	120					
	160					
	200					
	250					
	300					

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm
 = vertical panel joints

(panel width approx. 120 cm)

 = seamless

 = horizontal panel joint(s)

 = not available

AH = unit height

dimensions in cm

transolair Fabric pattern 338..
Fabric width 250 cm

		Awning width				
		100	150	200	250	300
AH	120					
	160					
	200					
	230					
	300					

perfortex Fabric pattern 331.. / 332..
Fabric width 120 cm

		Awning width				
		100	150	200	250	300
AH	120					
	160					
	200					
	250					
	300					

vuscreen Alu Fabric pattern 317..
Fabric width 252 cm

		Awning width				
		100	150	200	250	300
AH	120					
	160					
	230					
	250					
	300					

glass fibre screen Serge 600 Fabric pattern 272..
Fabric width 250 cm

		Awning width				
		100	150	200	250	300
AH	120					
	160					
	200					
	250					
	300					

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
 (panel width approx. 120 cm)
 = seamless
 = not available
 AH = unit height

= horizontal panel joint(s)

dimensions in cm

Soltis Veozip (not available) Fabric pattern 511..
Fabric width 290 cm

		Awning width				
		100	150	200	250	300
AH	120					
	160					
	200					
	250					
	300					

Soltis Perform 92 (not available)Fabric pattern 92-..
Fabric width 177 cm

		Awning width				
		100	150	200	250	300
AH	120					
	160					
	200					
	250					
	300					

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
(panel width approx. 120 cm)

= seamless
 = horizontal panel joint(s)

= not available

AH = unit height

dimensions in cm

sunvas	Fabric pattern	300.. – 315..	smart art	340..
transolair		339..	sunsilk	324.. / 328.. / 369..
perla FR		371.. ³⁾ / 372.. ³⁾		
Fabric width 120 cm				

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

sunvas	Fabric pattern	31008.. ¹⁾ , -09 ¹⁾ , -13, -16, -18, -25, -27, -28, -31, -36, -37, -57, -58, 31109, -14, -17
Fabric width 250 cm		

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	243							
	300				1)	1)	1)	
	350				1)	1)	1)	
	400				1)	1)		

1) also available in fabric width 320 cm – then seamless

sunbow	Fabric pattern	411.. - 427..
Fabric width 120 cm		

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
 (panel width approx. 120 cm)
 = seamless
 = not available
 AH = unit height

dimensions in cm

transolair Fabric pattern 338..
Fabric width 250 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	243							
	300							
	350							
	400							

perfortex Fabric pattern 331.. / 332..
Fabric width 120 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

vuscreen Alu Fabric pattern 317..
Fabric width 252 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	243							
	300							
	350							
	400							

glass fibre screen Serge 600 not available Fabric pattern 272..
Fabric width 250 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
 (panel width approx. 120 cm)
 = seamless
 = not available
 AH = unit height

dimensions in cm

Soltis Veozip (not available) Fabric pattern 511..

Fabric width 290 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

Soltis Perform 92 Fabric pattern. 92-..

Fabric width 177 cm

		Awning fixture width						
		150	180	250	300	350	400	450
AH	150							
	180							
	250							
	300							
	350							
	400							

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm= vertical panel joints
(panel width approx. 120 cm)

= seamless



= not available



= horizontal panel joint(s)

AH = unit height

dimensions in cm

sunvas	Fabric pattern	300.. – 315..	smart art	340..
transolair		339..	sunsilk	324.. / 328.. / 369..
perla FR		371.. ³⁾ / 372.. ³⁾		
Fabric width 120 cm				

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

sunvas	Fabric pattern	31008.. ¹⁾ , -09 ¹⁾ , -13, -16, -18, -25, -27, -28, -31, -36, -37, -57, -58, 31109, -14, -17
Fabric width 250 cm		

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	243							
	300				1)	1)	1)	
	350				1)	1)	1)	
	400				1)	1)		

1) also available in fabric width 320 cm – then seamless

sunbow	Fabric pattern	411.. - 427..
Fabric width 120 cm		

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
 (panel width approx. 120 cm)
 = seamless
 = not available
 = horizontal panel joint(s)
 AH = unit height

dimensions in cm

transolair Fabric pattern 338..
Fabric width 250 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	243							
	300							
	350							
	400							

perfortex Fabric pattern 331.. / 332..
Fabric width 120 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

vuscreen Alu Fabric pattern 317..
Fabric width 252 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	243							
	300							
	350							
	400							

glass fibre screen Serge 600 not available Fabric pattern 272..
Fabric width 250 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
 (panel width approx. 120 cm)
 = seamless
 = not available
 AH = unit height

dimensions in cm

Soltis Veozip (not available) Fabric pattern 511..
Fabric width 290 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

Soltis Perform 92 Fabric pattern. 92-..
Fabric width 177 cm

		Awning fixture width						
		150	180	250	300	350	400	450
AH	150							
	180							
	250							
	300							
	350							
	400							

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
(panel width approx. 120 cm)

= seamless

= horizontal panel joint(s)

= not available

AH = unit height

dimensions in cm

sunvas
transolair
perla FR

Fabric pattern 300.. – 315..
339..
371..³⁾ / 372..³⁾

smart art
sunsilk

340..
324.. / 328.. / 369..

Fabric width 120 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

sunvas

Fabric pattern 31008²⁾, -09²⁾, -13, -16, -18, -25, -27, -28, -31, -36, -37, -57, -58, 31109, -14, -17

Fabric width 250 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		243									
		300			2)	2)	2)				
		350			2)	2)	2)				
		400			2)	2)					
		450			2)	2)					
		500			2)	2)					
		550			2)	2)					
		600			2)	2)					

2) also available in fabric width 320 cm – then seamless

sunbow

Fabric pattern 411.. - 427..

Fabric width 120 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350	3)	3)	3)	3)	3)	3)	3)	3)	3)
		400	3)	3)	3)	3)	3)	3)	3)	3)	3)
		450									
		500									
		550									
		600									

3) Only in tracfix units

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

 = vertical panel joints

(panel width approx. 120 cm)

 = seamless

 = horizontal panel joint(s)

 = not available

AH = unit height

1) = optional

dimensions in cm

transolair Fabric pattern 338..
Fabric width 250 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		243									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

perfortex Fabric pattern 331.. / 332..
Fabric width 120 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

vuscreen Alu Fabric pattern 317..
Fabric width 252 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		243									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

glass fibre screen Serge 600 not available Fabric pattern 272..
Fabric width 250 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

 = vertical panel joints

(panel width approx. 120 cm)

 = seamless

 = horizontal panel joint(s)

 = not available

AH = unit height

1) = optional

dimensions in cm

Soltis Veozip (not available) Fabric pattern 511..

Fabric width 290 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

Soltis Perform 92 Fabric pattern. 92-..

Fabric width 177 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		180									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

 = vertical panel joints
(panel width approx. 120 cm)

 = seamless
 = horizontal panel joint(s)

 = not available
AH = unit height

1) = optional

dimensions in cm

sunvas
transolair
perla FR

Fabric pattern

300.. – 315..
339..
371..³⁾ / 372..³⁾
smart art
sunsilk
340..
324.. / 328.. / 369..

Fabric width 120 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

sunvasFabric pattern 31008²⁾, -09²⁾, -13, -16, -18, -25, -27, -28, -31, -36, -37, -57, -58, 31109, -14, -17

Fabric width 250 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		240									
		300			2)	2)	2)				
		350			2)	2)	2)				
		400			2)	2)					
		450			2)	2)					
		500			2)	2)					
		550			2)	2)					
		600			2)	2)					

2) also available in fabric width 320 cm – then seamless

sunbow

Fabric pattern 411.. - 427..

Fabric width 120 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350	3)	3)	3)	3)	3)	3)	3)	3)	3)
		400	3)	3)	3)	3)	3)	3)	3)	3)	3)
		450									
		500									
		550									
		600									

3) Only in tracfix units

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm
 = vertical panel joints

(panel width approx. 120 cm)

 = seamless

 = horizontal panel joint(s)

 = not available

AH = unit height

1) = optional

dimensions in cm

transolair Fabric pattern 338..
Fabric width 250 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		240									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

perfortex Fabric pattern 331.. / 332..
Fabric width 120 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

vuscreen Alu Fabric pattern 317..
Fabric width 252 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		243									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

glass fibre screen Serge 600 (only available with tracfix) Fabric pattern 272..

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

 = vertical panel joints

(panel width approx. 120 cm)

 = seamless

 = horizontal panel joint(s)

 = not available

AH = unit height

1) = optional

dimensions in cm

Soltis Veozip (not available) Fabric pattern 511..

Fabric width 290 cm

		Awning fixture width									
		150	200	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		200									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

Soltis Perform 92 Fabric pattern. 92-..

Fabric width 177 cm

		Awning fixture width									
		150	180	250	300	350	400	450	500	550	600
AH	tracfix 1)	150									
		180									
		250									
		300									
		350									
		400									
		450									
		500									
		550									
		600									

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

 = vertical panel joints
 (panel width approx. 120 cm)

 = seamless
 = horizontal panel joint(s)

 = not available
AH = unit height

1) = optional

dimensions in cm

sunvas
transolair
perla FR

 Fabric pattern 300.. – 315..
 339..
 371.. / 372..

smart art
sunsilk

 340..
 324.. / 328.. / 369..

Fabric width 120 cm

		Awning width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

sunvasFabric pattern 31008²⁾, -09²⁾, -13, -16, -18, -25, -27, -28, -31, -36, -37, -57, -58, 31109, -14, -17

Fabric width 250 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	243							
	300				2)	2)	2)	
	350				2)	2)	2)	
	400				2)	2)		

2) also available in fabric width 320 cm – then seamless

sunbow

Fabric pattern 411.. - 427..

Fabric width 120 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm
 = vertical panel joints

(panel width approx. 120 cm)

 = seamless

 = horizontal panel joint(s)

 = not available

AH = unit height

dimensions in cm

transolair Fabric pattern 338..
Fabric width 250 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	243							
	300							
	350							
	400							

perfortex Fabric pattern 331.. / 332..
Fabric width 120 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

vuscreen Alu Fabric pattern 317..
Fabric width 252 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	243							
	300							
	350							
	400							

glass fibre screen Serge 600 Fabric pattern 272..
Fabric width 250 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
 (panel width approx. 120 cm)
 = seamless
 = horizontal panel joint(s)
 = not available
 AH = unit height

dimensions in cm

Soltis Veozip (not available) Fabric pattern 511..
Fabric width 290 cm

		Awning fixture width						
		150	200	250	300	350	400	450
AH	150							
	200							
	250							
	300							
	350							
	400							

Soltis Perform 92 Fabric pattern. 92-..
Fabric width 177 cm

		Awning fixture width						
		150	180	250	300	350	400	450
AH	150							
	180							
	250							
	300							
	350							
	400							

Note: The maximum width of the outer panels in tracfix systems with vertical panel joints is 35 cm

= vertical panel joints
(panel width approx. 120 cm)

= seamless

= horizontal panel joint(s)

= not available

AH = unit height

dimensions in cm

